

Declaration of Performance

Isotal

Number of Declaration of Performance:

01 P5001 Isotal

1. Unique identification code of the product-type:
P5001 Isotal
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):
P5001 Isotal
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:
Grouting mortar
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):
Kema Puconci d.o.o.
Puconci 109
9201 Puconci, Slovenia
Production No.: P5001
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):
-
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 2+
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:
SIST EN 1504-3
ITC Institute for testing and certification Inc., Zlin, 1023
(name and identification number of the notified body, if relevant)
performed Initial type test **under system** 2+
(description of the third party tasks as set out in Annex V)
and issued **Product Type Examination Report No.: 753500230 TR2/2009,**
Certificate of Internal Control No.: 1023-CPR-0139F
(certificate of constancy of performance, certificate of conformity of the factory production control, test/calculation reports – as relevant)
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

-
 (name and identification number of the Technical Assessment Body, if relevant)

issued -
 (reference number of the European Technical Assessment)

on the basis of -
 (reference number of the European Assessment Document)

performed - **under system** -
 (description of the third party tasks as set out in Annex V)

and issued -
 (certificate of constancy of performance, certificate of conformity of the factory production control, test/calculation reports – as relevant)

9. Declared performance:

Essential characteristics	Performance	Harmonized technical specification
Classification:	R4	EN 1504-3
Compressive strength:	≥ 45 MPa	EN 12190
The content of soluble chlorides:	≤ 0,05 %	EN 1015-17
Bond strength:	≥ 0,8 MPa	EN 1542
Carbonation resistance:	Complies	EN 13295
Pull-out force	38 kN	EN 1881
Thermal compatibility, the reaction after 50 cycles of freezing - thawing:	NPD	EN 13687-1
Reaction to fire class:	Eurockass A1	EN 13501-1
Dangerous substances:	Complies	See material safety data sheet (MSDS)

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Chief of department of development and quality:

Stanko Polajner univ.dipl.inž.met.

Puconci, 12.12.2013



KEMA Puconci d.o.o.