

CERTIFICATE OF QUALITY KEMASOL

Emulsion for setting capillary moisture barriers

PRODUCT DESCRIPTION

Silicone emulsion for capillary moisture barriers in brick, stone and mixed material walls, carried out by drilling and impregnating the wall along the entire cross-section.

FIELD OF USE

KEMASOL is satisfactory for use to provide a barrier against rising damp in existing solid walls of brickwork, blockwork or stone (excluding flint), or existing walls of conventional cavity construction, where there is no dampproof course or where the existing dampproof course has failed.

PRODUCT DATA

Appearance	Colourless to softly yellow liquid
Packing	1 kg in plastic can / 8 kg (8x1 kg) in cardboard box / 576 kg (72x8 kg) on pallet 10 kg in plastic can / 600 kg (60x10 kg) on pallet 50 kg in barrel / 800 kg (16x50 kg) on pallet 1000 kg in container (rinfuza) ON ORDER
Storage and expiration date	12 months from the day of manufacture when stored properly in dry place and in the original, sealed and undamaged packaging. Manufacture date is stamped on the packaging.
Technical data	
Type of product	silicon emulsion on base pottassium methylsiliconate
Density	1-1,06 g/cm ³
Solubility in water	yes

TEST REPORT

The document was issued with the intention to prove the quality of the product according to specific requirements.

Puconci, 01.07.2015

Head of R&D:

Stanko Polajner, univ.dipl.ing.met.



KEMA d.o.o.
1